

SERBIATRIB '19

16th International Conference on Tribology



Faculty of Engineering University of Kragujevac

Kragujevac, Serbia, 15 – 17 May 2019

DETERMINATION OF THE OPTIMAL VEHICLE MAINTENANCE STRATEGY AS ONE OF THE CONDITIONS OF IMPROVING THE SAFETY OF TRAFFIC

Vojislav KRSTIĆ¹, Boris ANTIĆ²

^{1,2)} Faculty of transport and traffic engineering, University of Belgrade, Beograd, Serbia, bkrstic@kg.ac.rs, mpeeric@gmail.com

Apstract: Two types of preventive maintenance are mostly used. First is preventive maintenance based on reliability information (on empirically defined distribution of possibility of work time until breakdown). By application of this type of preventive maintenance, maintenance procedure is planned in order to provide required level of reliability, most often by preventive replacements after a definite work periodicity. Other type of preventive maintenance is based on connection of information about reliability and information acquired in view of constant and systematic follow-up of vehicle (follow-up of selected parameters and indicators that with enough security show its condition).

Strategy of total productive maintenance is based on statement that only by maintenance it is not possible to maintain projected level of reliability during exploitation, but it is necessary to have active participation of users and everyone who is in relation to the maintained vehicle.

Main application of so-called accelerated strategies of maintenance is not to conduct any activity of preventive maintenance if it is not economically justifiable.

Nowadays there is a tendency towards combined application of existing strategies of maintenance. The reason is placed in variety of maintained vehicles. Second reason is existence of flaws of current strategy for maintenance.

By application of knowledge based system, or so-called soft computing, we come to efficient methods used for treatment of problems while maintenance of technical systems, from the aspect of imprecision. One of such systems is fuzzy logic.

Essence of traditional and modern strategy of motor vehicle maintenance is analyzed. Special attention is given to modern strategy of motor vehicle maintenance.

Keywords: vehicles, maintenance, fuzzy logic

1. INTRODUCTION

Path of development of motor vehicle maintenance may be divided in several stages and they are as follows:

- First (from the first usage of motor vehicles to 1950), which main essence is to remove breakdown when it appears;
- Second (from 1950 to 1980), which main characteristics are lower maintenance costs, longer durability and greater disposability of motor vehicles;
- 3. Third (from 1980 and now), which main characteristics are better relation of effect and cost, longer duration, conservation, higher reliability and

disposability. Nowadays so-called classical strategies of maintenance are still dominating (corrective, preventive and its combination). Preventive maintenance is mostly performed according to time (vehicle is stopped it does not transport, its technical state is defined, and necessary and planned replacements are done). Regarding used techniques primarily during maintenance management, several stages of its application may be noticed:

- First (fix the breakdown when it appears);
- Second (planning, introduction of system for planning and work control and introduction of information technology);
- Third (taking care of reliability and facilities for maintenance during projecting of motor development vehicles, and follow-up of the condition of maintenance equipment, elaboration of risk study, usage of systems expert and microcomputer network, application of methods for vehicle analysis from the aspect of failure occurrence - FTA, FMECA, planned experiment and introduction of flexible service systems).

In the area of motor vehicle maintenance. importance of application of the theory of reliability, from the 40s of the 19th century, should be specially emphasized, esp. when it comes to defining regularity of breakdown appearance based on data about vehicle exploitation. Introduction of concept of integral logistic support and facilities of maintenance in the area of motor vehicle maintenance, during the 40s of the 19th century, is also significant for the development of science and maintenance practice. Introducing previous mentioned scientific knowledge enabled introduction of the strategy of maintenance according to reliability and total productive maintenance in the 70s of the 19th century.

Selection of maintenance procedures (preventive, corrective) that should be implemented during the motor vehicle maintenance, in order to provide their maximum reliability and disposability, is in often called literature conception of maintenance. Instead of term conception of maintenance, other terms are used as well: maintenance, policy of strategy of maintenance, system of maintenance. Nowadays many products are applied and their work is based on the fuzzy logic application.

It is performed in the field of forming fuzzy database, sample recognition, decision-making processing of native language, system, technology of development of fuzzv computers, fuzzy chips - fuzzy hardware, process and operation management in factories, realization of intelligent robots with the possibility to understand native language, understanding of scenes, with possibility to plan and control movement. It is performed in the field of usage of intelligent user's interface, cooperative work of people and robots, on adaptive fuzzy neuro systems, which can be adjusted to changeable conditions in the surrounding. Nowadays it is obvious that fuzzy logic can be applied in all fields of human performance.

Introduction of information system for easier acquisition and data processing during motor vehicle maintenance represents a great improvement in its maintenance system. It often occurs that objective conditions do not permit gathering of information necessary for statistic processing. If one bears in mind that gathering such information brings some expenditure, that is often a reason for impossibility to gather relevant information. In case when there are no high quality information, information that are incomplete and imprecise are used. It is a particular problem that is difficult to solve.

Application of knowledge-based system, socalled soft computing, enables efficient methods to treat the maintenance problem

from the aspect of imprecision. One of such systems is fuzzy logic. Fuzzy logic is rarely used individually. Mostly its application is combined with neuro computing, genetic computing and expanding the possibility of expert systems. Application of fuzzy logic enabled many improvements, in large number of fields of human performance. Great possibilities of its application should be used in the systems of technical system maintenance. Objective of the work is a review of essence of classical and modern strategies of motor vehicle maintenance, with detailed review of fuzzy application during vehicle logic motor maintenance.

2. STRATEGIES OF MOTOR VEHICLE MAINTENANCE

At modern level of science and technology development, the greatest attention is dedicated to two strategies of maintenance [1], and they are: maintenance according to reliability and total productive maintenance.

Methodology of maintenance according to reliability is based on modern scientific knowledge, mainly from the field of reliability and system science. Essence of this methodology is studying of vehicle behavior, mainly from the aspect of breakdown when used, with term and content adjustment of maintenance procedure. According to this methodology, maintenance is performed in view of recognition of reliability characteristics that are used for future state forecast, i.e. breakdown is foreseen. According to reliability characteristics of the vehicles, decisions about implementation of preventive maintenance are made (in order to prevent or postpone occurrence of sudden breakdown) and about procedure of corrective maintenance that is necessary to apply.

Main objectives of application of the methodology of maintenance according to reliability and safety of vehicles are:

 Providing reliability and safety of vehicles maintained on the level defined during development and production. When breakdown occurs, vehicle should be returned into primary level of reliability and safety.

 Gathering data about vehicle behaviour while used and taking over particular measures for improvement of its quality.

Previously mentioned objectives should be fulfilled with little costs (taking into account costs of maintenance and costs of occurrence of breakdown).

Application of methodology of total productive maintenance is based on the estimation of current condition of maintained vehicle. With application of this methodology it is provided to implement maintenance when it is necessary and not only when breakdown occurs, which resembles to the conception of preventive maintenance according to condition. In contrast to the conception of preventive maintenance according to condition, based on database of reliability, methodology of total productive maintenance is based on data from everyone who is in contact with the vehicle. For its application, it is necessary to have a domestic relation of experienced users towards to the vehicle. Implementation of this methodology does not exclude usage of reliability data, but it only insists on complete responsibility of all subjects that are in any way in contact with the vehicle.

During motor vehicle maintenance, the key problem is to avoid consequences of breakdown, but not prevent the occurrence of breakdown.

In existing literature from the field of "advanced" strategies maintenance, of maintenance are mentioned. By these strategies, it is tried to remove the flaws of other strategies. From these strategies, mostly are mentioned the following: PMO (Preventive Maintenance Optimization). Application of this strategy it is necessary to realize the following basic activities: defining of tasks of preventive maintenance; analysis of all breakdowns; analysis of consequences of arisen breakdown; definition of maintenance strategy. Objectives application of this strategy of are: rationalization of preventive maintenance procedure (implement only those that are appropriate and technically and economically justifiable, with optimization of periodic implementation); including equipment that enables maintenance according to condition; sharing of work on maintenance between maintainer and user.

Beside previously mentioned strategy, other strategies are mentioned in this group: methods based statistic on standard MILSTD2173 and method Cost Minimization Algorithm Program. It is envisaged [2] that in the future large application will have a socalled strategy of precise approach, based on removing of the cause of breakdown occurrence (if there is no cause for breakdown occurrence, breakdown will not happen), and then there is no need for maintenance. Such future is also envisaged for the strategy of total preventive maintenance (so that the vehicle implements itself adequate maintenance procedure).

3. PERFORMANCE INDICATORS OF THE VEHICLE MAINTENANCE SYSTEM

Nowadays it is spoken about successful system of motor vehicle maintenance if the following indicators are evident:

- Planned jobs in maintenance are much larger scale (over 90%), in relation to unplanned maintenance;
- Existing capacities for maintenance (equipment and personnel) are correctly engaged (usage of capacities is more than 70%);
- There is an optimum amount and assortment of spare parts and material in warehouse;
- Preventive maintenance is done when it is cheaper than corrective and without excluding exploitation vehicles;
- Planned activities of motor vehicle maintenance are done in due time;
- There is precise and accurate database necessary for realization of strategy of maintenance;
- Usage and maintenance of equipment is adequate;

- There is an adequate staff that participates in the realization of motor vehicle maintenance, with constant improvement of knowledge;
- There is maximum of people security that is involved in the realization of tasks of maintenance.
- Without usage of integral logistic support, esp. CMMS (Computerized Maintenance Management System), we cannot speak about possibility of application of modern strategies of motor vehicle maintenance.

Usage of information system for management of motor vehicle maintenance provides data necessary for application of modern strategy of maintenance. These data are useful for the realization of the following activities:

- Organization of maintenance jobs (type of jobs, plans, stop, costs, labor, equipment, material, spare parts, documentation);
- Labor arrangement (according to tasks, skill...);
- Realization of training, studying and giving instructions to staff working at motor vehicle maintenance;
- Generating of work order for realization of preventive maintenance, mainly in view of follow-up of all requirements for maintenance and given resources;
- Classification of maintenance tasks according to priorities, location...);
- Analysis of income and expenses;
- Selection of most suitable offer of spare parts and materials used for motor vehicle maintenance (owing to existing of data basis about manufacturers, quality and prices of spare parts and materials);
- Follow-up and analysis of breakdown of equipment used for maintenance;
- Realization of statistical analysis and data processing in order to acquire information that provide adequate management of maintenance;

- Increase of safety of personnel and equipment while motor vehicle maintenance;
- Follow-up of realization of taken obligations by adequate contracts about maintenance and realization of transport work.

According to acquired data by application of information system for maintenance management, analysis of adequacy of strategy for motor vehicle maintenance can be done (evaluation and defining of current problems when implemented).

Evaluation of the strategy for motor vehicles is done in view of responses to the following questions:

- Is preventive maintenance done in due time and what are the results of its realization?
- Are the plans and programs of preventive maintenance adequate (what is a relation between work on the realization of preventive and corrective maintenance, legality of appearance of corrective maintenance during time...)?
- For realization of which activities is most time spent?
- For realization of which activities of maintenance are most investments needed and what are the costs of maintenance?
- What is the scale of unrealized tasks of maintenance, esp. those that are taken over by contracts?
- What are the common problems in maintenance?

Information system for management of motor vehicle maintenance is satisfying if it does the following:

- Generates output documents in a useful way;
- Gives review of labor arrangement (according to tasks, skill...);
- Gives review of available equipment for motor vehicle maintenance (according to location, condition, belonging to organizational entireties, possibilities...);

- Gives review of available supplies (minimum and maximum level of supplies in parts, current condition in segments, locations);
- Gives work orders in a satisfactorily way;
- Analyze preventive maintenance procedure (needed resources);
- Gives feedback about effectiveness of done maintenance procedure and technical condition of motor vehicles.

In order to achieve maximum of effectiveness of usage of motor vehicles, in future there will be more attention given to their maintenance, both through improvement of maintenance system, and increased engagement of those who are involved in their development, production and exploitation.

Previously given activities may be expressed in a following way:

- Connection between manufacturer and user of equipment for maintenance with the manufacturers of motor vehicles;
- Application of adequate methodologies when defining strategy of motor vehicle maintenance, which shall give best results in given conditions;
- Application of adequate equipment for motor vehicle maintenance;
- Increase in implementation of IT in detection, diagnostics and foreseeing of breakdown (by usage of decisionmaking support system, expert's system, artificial intelligence....);
- Increased level of knowledge of all participants in motor vehicle maintenance;
- Application of strategy for motor vehicle maintenance without breakdown, primarily owing to removing cause of possible breakdown.

4. APPLICATION OF FUZZY LOGIC BY MOTOR VEHICLE MAINTENANCE

Words: indistinct, imprecise, undefined, indefinite, ambiguous, diffuse, vague, confused could be substituted by a single word.

It is a word fuzzy, which has an English origin. Professor of Computer Science at California University in Berkley, LoftiZadeh, is a founder of fuzzy logic.

He is considered to lay foundations for it in 1965. According to him, fuzzy logic can have two different meanings. In wider sense, fuzzy logic is a synonym for the theory of fuzzy groups, related to objects with vague borders measured by certain degree. In inner sense, fuzzy logic is a logic system that is an extension of classical logic. Essence of fuzzy logic is in many ways different from the essence of socalled traditional logic. Fuzzy logic uses the principle of incompatibility, which means tendency that with the increase of imprecision of statement it comes to its relevance. Fuzzy logic is multivalued logic that enables medium values defined between traditional opinions: true-false, yes-no, black-white etc. Fuzzy logic uses experiences of experts in the form of linguistic rules if-then, and mechanism of approximate reasoning is used as a control for definite case. Key aspect of application of fuzzy logic is development of theory which formalizes everyday informal opinion that can be used for computer programming.

In order to explain previously mentioned, we would shortly explain difference between fuzzy system and theory of possibility.

Those who do not recognize the essence and possibility of fuzzy logic application often ask the following question: "Can a process be controlled by using the vague method?" Where there was no perplexity about the answer to this question, fuzzy logic had turbulent development in almost all fields of human life. Nowadays, Japan is a leader in fuzzy logic application.

Fuzzy technology represents effort to imprecise information present and process by computer. That is a way to enable closer connection between man and computer. It enabled it to categorize to so-called humane technologies.

From Japan, by the professor from Tokyo Institute for Technology, Toshiro Terana, and professor from University for telecommunications in Osaka, KjodjiAsaia, there was an idea for broad usage of fuzzy logic as an engineer tool. Nowadays, fuzzy engineering has developed into a powerful scientific branch. In all segments of computing, fuzzy logic application is present today. Owing to its application, systems which use fuzzy technology within fuzzy database are realized, fuzzy systems for qualitative modeling, for fuzzy data analysis, fuzzy identification of system and data generalization, recognition of forms, fuzzy data analysis, fuzzy system for image process, development of intelligent interface and other computing fields.

Development of fuzzy idea is long-term, and its roots originate from far antique days, from Pluto and Aristotle. There are many famous persons, in a long chain of development of that contributed fuzzv idea, to the development of this idea, and on whose knowledge is based the learning of the founder of fuzzy logic and those who succeeded in implementation of its systems that have a base in fuzzy logic application. It is interesting that in that chain is the name of Verner Heisenberg, who defined the principle of uncertainty in 1927, and Max Black, who defined now called function of belonging in 1937. Professor Zadeh finally formulated theory of fuzzy logic, on which all developed systems are based. Basis of his theory is understanding that instead of rigorousness and tendency for greater precision of description and thinking about appearances, one should move in opposite direction, i.e. descriptions should be imprecise. Historical facts in development and application of fuzzy logic are also: development of first industrial fuzzy controller in London in 1974, first application of fuzzy controller for management of cement production in 1980. In 1987 began work of first subway with fuzzy the management. In 90s of the 19th century, many products whose work was based on application of fuzzy logic appeared on the market. Intensive work in this field was continued because of amazing results of application of fuzzy logic. It is about the field of forming intelligent users' interface, cooperative work between people and robots, adaptive fuzzy neuro that can be adjusted to changeable conditions. Nowadays it is obvious that fuzzy logic may be applied in every field of human performance. Previously mentioned facts seem impressing.

If we wanted to tell something more about fuzzy logic shortly, we could tell the following: principle of humanity in engineering is necessity of application fuzzy engineering depends on how much engineer takes care about man when he develops each system. Principle of incompatibility is the more the realistic problem is viewed, the more its solution becomes fuzzy. Characteristics of fuzzy application, as a new approach to worlds gradualness, imprecision, usage are of qualitative description and expert's knowledge. Fuzzy technologies are humane technologies and represent relation between man and machine. Skill is received through practice, by learning and practicing. By using neuro technologies, training of computer systems can be done. By using fuzzy technologies expert's knowledge can be described and represented in a computer.

Advantages of application of fuzzy logic while maintenance of complex technical systems are:

- a) Fuzzy logic is conceptually easy to understand, because its mathematical outline of fuzzy reasoning is simple;
- Fuzzy logic is flexible it is possible to correct analyzed system in each movement without need to return to start;
- c) Fuzzy logic tolerates imprecise data, because it is based on existence of imprecise data;
- Fuzzy logic may modulate linear functions, it is possible to create fuzzy system that may be adjusted to any set of input-output data;
- e) Fuzzy logic may be used to describe expert's experience, for it leans on the experience of those who are excellent knowledge of analyzed system;
- f) Fuzzy logic is based on native language, for its basis is human communication.

Common sense should be used while using fuzzy logic and apply it only then when it is possible to get effective solution – unless there is a simpler way to solve the set problem.

Classical logic uses phrases that are whether totally incorrect or completely correct. Fuzzy logic represents extension of classical logic. It actually represents multivalued logic. It means that phrase is with a definite level of correctness.

Group of elements with the *same* qualities is called classical - discreet group. It means that every element of discreet group belongs to that group 100%. Each element of discreet group belongs to that group with level from 1, on a scale from 0 to 1.

In fuzzy technologies, fuzzy group is a basic element for introduction and processing of imprecision. It represents extension and generalization of classical discreet group. That is actually a group of elements with similar qualities. Each element belongs to fuzzy group in a certain degree. By fuzzy function of belonging, level of belonging to some fuzzy group is described. With different levels of belonging, element can be placed in several groups. In that case, overlapping of intervals of confidence in those groups occurs. Input function of belonging can have discreet or continuating values. In continuating intervals of confidence, by means of parameters, function of belonging is defined. In the form of vectors, with definite number of parameters, discreet function of belonging is defined. In that case, it is necessary to specify range of confidence interval and level of each point.

Element of fuzzy group is each element in confidence interval with a definite degree of belonging. There are two questions while forming fuzzy groups: How many fuzzy groups are necessary and sufficient? How to choose definite function of belonging? Response to those questions is: by experience. Definite number of functions (false) of belonging can use program package Mat lab: triangular, trapezoid, linear, bell-like etc. In many cases standard functions of belonging are used: Z – type, Λ - type (lambda), Π - type (pi), and S – type. These functions are always normalized, so their maximum is always 1, and minimum 0. Since fuzzy groups are extension of classical groups, union, section or complement operational are used as modifiers of function of belonging. They are defined by operators. Union is defined by maximum operator, and section by minimum operator.

In fuzzy logic, linguistic objects are words, not numbers. Linguistic phrases represent relation between numeral representation of computer data and way of man's thinking[3]. For example, if variable quality of maintenance can have following values: good, bad, not bad, very good, more-less good, then the quality of maintenance is linguistic variable. In that case, good, bad, not bad, very good, more-less good are called values of linguistic variables or linguistic values. Also, more or less, similar phrases are called linguistic modifiers.

Group of rules where words describe solution to a problem is called base of rules or expert's rules. In order to easily understand, rules are written in adequate order.

Group of rules may be represented not only in form if-then, but in more compact presentation, in so-called relation form, or more compact in table linguistic form.

If input fuzzy variables are first input and second input, then this format is called linguistic fuzzy plan. Graphical format is used which shows curves of the functions of belonging (picture 1).

Mechanism of conclusion is a mechanism of approximate reasoning. It is a three-phase process: aggregation, activation and accumulation.

First step in solving some problem in fuzzy systems is fuzzification. It is a process that converts each numeral input data in a level of belonging, examining one or more functions of belonging. There is a level of belonging for each linguistic variable, applied on definite input size.

By aggregation there is a process of joining definite values of the function of belonging to the measured numerical value, that is, definition of confidence level (level of truth) of dome input numerical value has the belonging to given fuzzy group. Aggregation is equivalent to fuzzification when there is only one input. In every group, it can be realized with how much truthfulness each rule applies.

Activation is a conclusion made in a part of rule. It is actually deduction of conclusion. As an activated operator min or algebra product is used, mostly used methods of direct conclusion - Mamdani's methods. At those forms of conclusion, only true premises are taken into account. By application of these methods, fuzzy groups are in input and output. Takagi-Sugeno-Kang method does not differ from other methods of direct concluding, but there is a great difference in structure of fuzzy rules. There is a difference that in conclusion instead of fuzzy groups there is a linear function between input and output, Often used case is when linear coefficients are equal to zero and then function of belonging is known as singleton.

Accumulation consists of activating of conclusion that is accumulated by addition. As an accumulative operator max or algebra total is used. By approximate reasoning (e.g. minmax), it is necessary to emphasize which method is used.

During defuzzification, resulting fuzzy group converts into number. The following methods of defuzzification are used: 1. COG - Centre of gravity or COA - centriod of area. Output numeral value is abscise of the center of gravity of fuzzy group; 2. COGS - Centre of gravity method for singletons. This method has a relatively good computer complexity, and is differentiable in relation to singleton, which is useful in neurofuzzy systems; 3. BOA - Bisector of area; 4. MOM - Mean of maximum. Searching for the point which has max belonging is basis of intuitive access. If there are few maximums, then we search for the mean of maximum. This method disregards form of fuzzy group, but its computer complexity is good. It is often used in problems of recognition forms and classification; 5. LM -Leftmost maximum is greatest on RM -Rightmost maximum.

Next possibility is selection of largest maximum on right or left side. In case of

robot movement management, it must be chosen between left and right, in order to avoid obstruct in front of him. Defuzzificator must choose one or other, and not something between. This method is indifferent to form of fuzzy group, but its computer complexity is small.

Fuzzy reasoning does not insist on sophisticated techniques of defuzzification. It requires great flexibility while forming rules, which is not a case when applied in automatic management, that is, in fuzzy control.

This analysis is done in order to see the influence of selection of function of belonging and its order, on output, or group of possible solutions. Two-dimensional table is caused by two inputs and one output. It can be drafted as a surface suitable for visual examination. Relation between one input and one output can be drafted as a graph of function. Graphs help when selecting functions of belonging and forming of rules. Surface form may be controlled to a certain degree by functions of belonging.

Fuzzy controller is a central part of configuration for management of motor vehicle. Fuzzy controller can be realized by program that is performed on PC and is connected to the process in a usual way, as in classical management. In that case, fuzzy controller is used for intelligent management, so that the knowledge of expert-operator is used in management. When it is necessary, fuzzy controller can be built as а microprocessor in smaller devices.

Possibilities of application of fuzzy logic are enormous. Let us mention some of examples of application of fuzzy controller on motor vehicles in Japan and Korea, countries that are leaders in practical application of fuzzy technologies.

Fuzzy brakes (Nissan): manages breaks in dangerous situations in view of speed and acceleration of vehicles, and in view of speed and acceleration of wheels.

Engine of the car (NOK, Nissan): manages fuel injection and ignition depending on condition of valve for fuel supply, oxygen flow, temperature of cooling water, number of rotationper minute, fuel volume, crankshaft, vibration of motor and pressure in absorb branch.

Transition system in car (Honda, Nisan, Subaru): selection of level of transition depending on motor pressure, way of driving and road conditions.

Management of vehicle movement (Isuzu, Nissan, Mitsubishi): adjust valve for fuel supply in view of speed and acceleration of vehicle.

Beside given examples of application of fuzzy management, there is also a large number of fuzzy management systems used motor vehicle. Also, beside large on application on motor vehicles, fuzzy controllers have found great implementation in medicine (diagnosis of illness), traffic (management of crossroads), house devices etc.

5. CONCLUSION

Two types of preventive maintenance are mostly used. First is preventive maintenance based on reliability information (on empirically defined distribution of possibility of work time until breakdown). By application of this type of maintenance, maintenance preventive procedure is planned in order to provide required level of reliability, most often by preventive replacements after a definite work periodicity. Other type of preventive maintenance is based on connection of information about reliability and information acquired in view of constant and systematic follow-up of vehicle (follow-up of selected parameters and indicators that with enough security show its condition).

Strategy of total productive maintenance is based on statement that only by maintenance it is not possible to maintain projected level of reliability during exploitation, but it is necessary to have active participation of users and everyone who is in relation to the maintained vehicle.

Main application of so-called accelerated strategies of maintenance is not to conduct any activity of preventive maintenance if it is not economically justifiable. Nowadays there is a tendency towards combined application of existing strategies of maintenance. The reason is placed in variety of maintained vehicles. Second reason is existence of flaws of current strategy for maintenance.

Fuzzy logic application enables large advantage in many human activities. Large possibility of its application is to use in the systems of motor vehicle maintenance.

Aim of the work is a review, in the briefest form, of fuzzy logic base, some causes of uncertainty in the systems of motor vehicle maintenance and possibility of its application by maintenance.

In order to achieve maximum effectiveness of usage of motor vehicles, in future more attention will be given to their maintenance, both through improvement of maintenance system and increased engagement of those who participate in its development, production and exploitation.

Without integral logistic support, esp. information systems for management of maintenance, we cannot speak about possibility to apply modern strategy for vehicle maintenance.

By application of knowledge based system, or so-called soft computing, we come to efficient methods used for treatment of problems while maintenance of technical systems, from the aspect of imprecision. One of such systems is fuzzy logic. Fuzzy logic is rarely used individually. Mostly its application is combined with neuro computing, genetic computing and expanding the possibility of expert systems.

Application of fuzzy logic enabled many improvements, in large number of fields of human performance. Great possibilities of its application should be used in the systems of technical system maintenance.

Geometric model of management of process of preventive maintenance by fuzzy logic, which essence is showed in this work, should enable: defining of parameters in uncertainty of work of technical system; defining influence of specific parameters on the process of preventive maintenance of technical system; defining most influential parameter and order of activities that should be done, as defining moment to start preventive maintenance. Procedure of forming geometric model should be defined by maintenance manager, who is in authority of decision making about preventive maintenance of technical system.

Application of fuzzy logic during maintenance of technical system is justifiable by the fact that the model of maintenance is complex, esp. if it is taken into account that description of maintenance problem includes work and breakdown condition and also mid condition. By its application, we are closer to the goal of acquiring maximum readiness, effectiveness and minimal costs.

Essence of traditional and modern strategy of motor vehicle maintenance is analyzed. Special attention is given to modern strategy of motor vehicle maintenance.

REFERENCES

- [1] R. Babuška: *Fuzzy and neural control*, Delft University of Technology, Netherlands, 2001.
- [2] B. Krstić: Analysis of the vital parts of the engine vehicles on the base of the data from exploitation, VII International scientific conference, Simulation Research in Automotive Engineering, Lublin, Polska, 1999.
- [3] B. Krstić: Determination of the optimal strategy for preventive maintenance the motor engine using policriterion optimization, International Journal for Vehicle Mechanics, Engines and Transportation Systems, Mobility Vehicles Mechanics, Vol. 29, No. 4, pp. 15-24, 2003.
- [4] B. Krstić: Determination of the optimal strategy for preventive maintenance of the clutch motor vehicles using polycriterion optimization, *Third International Tribology Conference ITC* 2004, Z. Gora, Poland, 2004.
- [5] B. Krstić: Analysis of the reliability of the motor vehicle brakes bands and

determination the optimal periodicity for their preventive maintenance, International Tribology Conference CONAT 2004, Brasov, 2004. [6] BS5760 British Standard - Part 2 Guide to the assessment of reliability, Reliability of systems, equipment and components, 1981.